## Three Compartment Tanks

|                | 1850 3C<br>560 / 560 / 730 | 2250 3C<br>680 / 680 / 890 | 2675 3C<br>810 / 810 / 1,055 | 3000 LP 3C<br>1,000 / 1,000 / 1,000 | 5000 LP 3C<br>1,675 / 1,675 / 1,650 |
|----------------|----------------------------|----------------------------|------------------------------|-------------------------------------|-------------------------------------|
| Lead Time      | Stock                      | Stock                      | Stock                        | 3 - 4 Weeks                         | 3 - 4 Weeks                         |
| Inlet Invert   | 53"                        | 63"                        | 74"                          | 46"                                 | 68"                                 |
| Outlet Invert  | 50"                        | 60"                        | 71"                          | 44"                                 | 66"                                 |
| Length         | 120"                       | 120"                       | 120"                         | 230"                                | 230"                                |
| Width          | 96"                        | 96"                        | 96"                          | 98"                                 | 98"                                 |
| Height         | 67"                        | 77"                        | 88"                          | 58"                                 | 80"                                 |
| Liquid Level   | 47" / 47"/ 46"             | 57" / 57" / 56"            | 68" / 68" / 67"              | 39" / 39" / 39"                     | 61" / 61" / 61"                     |
| GPI            | 12" / 12" / 16"            | 12" / 12" / 16"            | 12" / 12" / 16"              | 27.94 / 27.94 / 27.82               | 27.94 / 27.94 / 27.82               |
| Outlet Volume  | 564 / 564 / 736            | 684 / 684 / 896            | 816 / 816 / 1072             | 1,089 / 1,089 / 1,085               | 1,704 / 1,704 / 1,697               |
| Depth of Cover | 96"                        | 96"                        | 96"                          | 96"                                 | 96"                                 |

| Lead Time for standard product is defined as:                                | Liquid Level is measured from floor to outlet flow of each compartment. |  |  |
|--|---|--|--|
| Stock: Is available for delivery on a daily basis for quantities             | GPI expresses Gallons Per Inch for each compartment.                    |  |  |
| of 2 or less. For any orders of 3 or more, please place order 2 – 3 business | Volumes are expressed in Gallons.                                       |  |  |
| days in advance of required delivery date.                                   | Inlet Invert is measured from bottom of tank to bottom of PVC Pipe.     |  |  |
| Stock-1: Is available for delivery on a daily basis for a quantity of one.   | Outlet Invert is measured from bottom of tank to bottom of PVC Pipe.    |  |  |
| For any orders of 2 or more, please place order $2 - 3$ business days in     | Height is measured from bottom of tank to top of cover.                 |  |  |
| advance of required delivery date.   | Depth of Cover is maximum amount of cover over top of tank.             |  |  |
| Numerical: Expressed in weeks prior to required delivery date.               |   |  |  |
| Multiple Tank Orders: The tank with the longest lead time applies to         |   |  |  |
| the entire order.  |   |  |  |